

16 Gallon Compact Glycol Feed Unit

Glycol feed units are designed to provide an automated supply of water-glycol mix to a cooling or heating closed loop system. Units are assembled with easy plug and run capability. Units are compact and self-contained with a small footprint for ease of installation and operation.



S-16-PEFS-V:
Glycol Feed with
Pressure Regulating Valve

S-16-PEFS-P:
Glycol Feed with
Pressure Regulating Valve

Standard Features:

- **Low Voltage Operation:**
Unit includes a UL listed 115vac to 12vdc power supply and power indication light.
- **Pressure Pump:**
Self-priming diaphragm pump 12vdc. Capable of 1.1 gpm @ 40 psi
- **Low Level Cut-out Float Switch:**
System shutdown to prevent pump from running dry.
- **16 Gallon Tank:**
Tank is heavy duty polyethylene with graduated capacity scale and twist-on fill cap.

Options:

- **Digital Control (S-16-PEFS-V):**
Glycol systems are available with a digital controller with built-in dot-matrix display. High/Low pressure alarm adjustable to 39 PSI.

Skidmore®

1875 Dewey Avenue Benton Harbor, Michigan 49022

Phone 269.925.8812 <http://skidmorepump.com/>

MANUFACTURING AND DESIGN OF QUALITY HVAC SYSTEMS SINCE 1921