

Simplex 55 / 100 Gallon Free Standing Glycol Feed Unit

Glycol feed units are designed to provide an automated supply of water-glycol mix to a cooling or heating closed loop system. Units are factory engineered, assembled and tested with easy plug and run capability. Units are compact, self-contained with a small footprint for ease of installation and operation.



OPTIONS:

- HSP:** High Pressure 25-85 psi
- EHSP:** Extended High Pressure 35-125 psi
- PRVD:** Dual Discharge / Dual Loop
- ACP:** Alarm Control Panel

SPECIFICATIONS:

<u>MODEL</u>	<u>SIZE</u>	<u>VOLTAGE</u>	<u>PRESSURE</u>
EGF-55	Simplex 55 Gallon	110vac / 1PH / 60hz	8-50 psig System Pressure
EGF-100	Simplex 100 Gallon	110vac / 1PH / 60hz	8-50 psig System Pressure

STANDARD FEATURES:

- **Unit Operation**

Plugs into a standard 110 vac outlet

- **Pressure Pump**

Self priming diaphragm pump 100 psi @ 1.0 gpm ul /cul listed.

- **Low Level Cut-out Float Switch**

System shut-down to prevent pump from running dry.

- **55 / 100 Gallon Tank**

Tank is heavy duty polyethylene with graduated capacity scale and lift off fill cap.

- **Discharge and Suction Piping**


Includes suction strainer, brass check valve, pressure gauge, mixing purge valve, and 36" flexible system connection hose.

- **System Pressure Regulating Valve**

Valve is field adjustable (8-50 psig) with integral replaceable strainer.

- **Accumulator Tank**

2 gallon tank is rated for 125 psi and is pre-charged for ease of installation.



The specifications contained in this bulletin were effective at the time of publishing. We reserve the right to discontinue products at any time or to change specifications or design without incurring any obligation.



1875 Dewey Ave.
Benton Harbor MI 49022

TEL - (269) 925-8812
FAX - (269) 925-7888
www.skidmorepump.com